



RYLARD



Rylard Hull Coatings

1 pack systems

- Traditional single pack 'Blacking'
- A range of resin types and finishes
- Application by spray, brush or roller
- Specially formulated for canal boats
- Economic coatings for routine maintenance





Traditional Single Pack ‘Blacking’

Single pack coatings -
for economy and ease of use

Every coating choice is a balance between cost, performance and method/equipment of application.

These Rylard single pack hull coatings give **good performance** at the **lowest cost** with **easy application** properties.



Product	Type	Initial Finish	Volume Solids	Overcoating Time at 20°C
RYTEX	Bodied bitumen	Satin	47%	16 hr
PREMIUM PROTECTION	Bitumen with Gilsonite	Glossy	38%	24 hr
UNIVERSAL HULL COATING	Thixotropic bitumen	Satin	52%	16 hr

- All Rylard single pack hull coatings can be applied by spray, brush or roller
- Launch Time for all products is 48 hours minimum after final coat (at 20°C)
- Rytex, Premium Protection and Universal Hull Coating are all bitumen based, and should only be topcoated with other bitumen coatings (with themselves is recommended)
- Products containing Coal Tar have been phased out of the European market due to changes in Health & Safety regulations. Coflex VT (vinyl tar) and Epicol CT (tar epoxy) are therefore no longer available, and Rytex should be used instead.

RYLARD PAINTS
Blackwell Road
Huthwaite
Nottinghamshire
NG17 2RG

T 01623 510585
W www.rylardpaints.co.uk
E sales-rylard@axalta.com

Jan 2019 issue