



RYLARD



Rylard Hull Coatings

1 pack systems

- Traditional single pack 'Blacking'
- A range of resin types and finishes
- Application by spray, brush or roller
- Specially formulated for canal boats
- Economic coatings for routine maintenance





Traditional Single Pack ‘Blacking’

Single pack coatings -
for economy and ease of use

Every coating choice is a balance between cost, performance and method/equipment of application.

These Rylard single pack hull coatings give **good performance** at the **lowest cost** with **easy application** properties.



Product	Type	Initial Finish	Volume Solids	Overcoating Time at 20°C
RYTEX	Bodied bitumen	Satin	47%	16 hr
PREMIUM PROTECTION	Bitumen with Gilsonite	Glossy	38%	24 hr
UNIVERSAL HULL COATING	Thixotropic bitumen	Satin	52%	16 hr

- All Rylard single pack hull coatings can be applied by spray, brush or roller
- Launch Time for all products is 48 hours minimum after final coat (at 20°C)
- Rytex, Premium Protection and Universal Hull Coating are all bitumen based and should only be topcoated with other bitumen coatings (with themselves is recommended)

RYLARD PAINTS
Blackwell Road
Huthwaite
Nottinghamshire
NG17 2RG

T +44 (0)161 775 3025
W www.rylardpaints.co.uk
E sales-rylard@axaltacs.com

April 2018 issue